



This MSA Compliant SFP transceiver provides 100Base-FX throughput up to 100m over a fiber connection using an LC connector. 100Base-FX Fiber SFP works at 850nm wavelength and 550 meters high.

**MSA and TAA Compliant 100Base-FX Fiber SFP Transceiver.**



**Fiber SFP Module  
100BASE-FX Fiber SFP**

**TECHNICAL SPECS**

**Product Type**  
SFP (mini-GBIC)

**Ethernet Technology**  
Gigabit Ethernet

**Interfaces/Ports Details**  
1 x 100Base-FX Fiber SFP

**Media Type Supported**  
Optical Fiber

**Network Technology**  
100Base-FX Fiber SFP

**Application/Usage**  
Data Networking

**Temperature**  
Operating: -40°C to +85°C

**Compatibility**  
MSA, TAA

It is also capable of withstanding rugged environments and can operate at temperatures between -40°C to +85°C. It is built to MSA standards and is uniquely serialized and data-traffic and application tested to ensure that they will integrate into your network seamlessly. It is built to meet or exceed the specifications of MSA Compliant, as well as to comply with MSA (Multi-Source Agreement) standards to ensure seamless network integration. All of our transceivers are Trade Agreements Act (TAA) compliant.

Part Number	Part Description
G0900249	100Base-FX Fiber SFP Transceiver

**Ordering Information CALL: (866) 652-3500**

Email: [sales@clearcube.com](mailto:sales@clearcube.com) to order or for more information

