



Outstanding User Experience Fiber Zero Client w/6 USB Ports and Dual Monitor Support.
Supports low speed USB peripherals including multiple monitors, keyboard, mouse, audio, and more.



CD7522/24M Zero Client

KEY FEATURES

Chipset
 Teradici TERA2321 PCoIP®

Display/Resolution
Single: 4K (3840x2160) through the Display-Port port
Dual: 1920x1200@60Hz, Color Depth: 8, 15, 16 or 24bpp

I/O Physical
 DisplayPort x 1
 Single-link DVI-I x 1
 3.5mm Headphone jack
 3.5mm Microphone jack
 Power button

Network
 LAN: SFP 100/1000Base-X

Operating System
 None

Accessories
 VESA Mounting Bracket (optional)

TECHNICAL SPECS

Weight
 1 lb (500gr)

Dimensions
 1.2 (H) × 6.5 (W) × 5 (D) in

Temperature
Operational: 0 to 40°C
Storage: -20 to 70 °C

Humidity
Relative (non-condensing): 10% to 90%
Storage: 5% to 95%

Power
Input: Universal 100-240 VAC, 50-60Hz
Output: 12V DC, 3A

Max Consumption
 8.4 Watts w/o USB, 26.78 with 6 USB devices attached

Physical Characteristics
 Metal housing

Security
 Integrated PKI approved smart card reader on CD7524M model
 Kensington security slot for use with Kensington locks

Regulatory Compliance
 TAA Compliant
 FCC, EC, UL, RoHS, GOST/CU/EAC

IDEAL FOR:

- State & Local Government
- IT Professionals
- Military & Defense
- Command & Control Centers
- Healthcare, Financial, & Insurance
- Call Centers

Part Number	Part Description
G09007522	CD7522M Zero Client
G0900397	CD7524M Zero Client w CAC reader

BENEFITS



Delivers full desktop quality computing experience via an IP connection to Blade PCs or VMware Horizon desktop with no noise, less heat, and smaller space requirements



4k monitor support for high performance multimedia



AES256-bit encryption & increases security of physical and data assets


Rear View

SIMPLE AND SECURE

An additional security feature on the CD7524M includes an integrated PKI-approved CAC reader that supports 5V, 3V, and 1.8V smart cards for enhanced user-to-network and user-to-application authentication and a 100/1000 BASE-X SFP fiber-optic network module (with LC optical interface) to provide increased data security and integrity.

FULL PC EXPERIENCE OVER IP

ClearCube® CD7522/24M delivers high performance and robust security in a PCoIP Teradici TERA2 computing solution unhindered by distance. The CD7522/24M Zero Client delivers full performance video on dual monitors and connects over fiber networks to VMware® virtual desktops, servers, Blade PCs or public cloud resources brokered by VMware Horizon. Traditional, dedicated 1:1 users (where one person uses one dedicated computer) can take advantage of hardware accelerated PCoIP host cards in ClearCube Blade PCs to support legacy, mission-critical, and GPU intensive applications.

The CD7522/24M Zero Client requires no special OS drivers, there are no moving parts that can fail and no removable parts that encourage user tampering or theft. The units support all low speed USB peripherals including multiple monitors, keyboard, mouse, audio input/output devices, and more.

HIGH PERFORMANCE, OPTIMAL QUALITY

The CD7522/24M's powerful TERA2321 chip supports AES-128/AES-256 Suite B Ciphers for exceptional security, one DisplayPort connector and one DVI-I connector, the CD7522/24M supports one display at 4K resolution (DisplayPort only), and two displays at 1920 × 1200 resolution, and full power management with Wake-on-LAN features.

Ordering Information CALL: (866) 652-3500

 Email: sales@clearcube.com to order or for more information
