

Future proof your display options.

6 USB 2.0 Ports (4 in front, 2 in back) with ability to independently configure monitors.



CD7526 Zero Client

IDEAL FOR:

- State & Local Government
- IT Professionals
- · Military & Defense
- Command & Control Centers
- · Healthcare, Financial, & Insurance
- · Call Centers

 $\overline{\mathbf{m}}$

KEY FEATURES

Chipset

Teradici TERA2321 PCoIP®

Memory Capacity/Type

8GB LPDDR4 dual-channel SDRAM memory, non-ECC

Storage

64GB soldered eMMC

Display/Resolution

Single: 2560x1600@60Hz: Color Depth: 8, 15, 16 or 24bpp Dual: 1920x1200@60Hz: Color Depth: 8, 15, 16 or 24bpp

I/O Physical

Single-link DVI-D × 1 Single-link DVI-I × 1 USB 2.0 × 6

3.5mm Speaker port × 1

3.5mm Microphone port × 1

3.5mm Headphone port × 1

Network

LAN: SFP, 10/100/1000 BASE-T, 100 BASE-FX, 1000 BASE-SX, 1000 BASE-LX

IPv6 Support (Tera firmware 5.0.0 and VMware Horizon 6.1)

TECHNICAL SPECS

Weight

2.5 lbs (1.13kg)

Dimensions

 $1.8 (W) \times 5.9 (H) \times 5.1 (D) in$

Environment

Stationary office installation, 0° to 35° C

Power

Universal 100-240 VAC, 50-60Hz Output: 12V DC Optional Power over Ethernet (PoE)

Max Consumption

8 Watts w/o USB; 26 Watts w/ 6 high power USB devices attached

Physical Characteristics

Plastic housing

Operating System

None

Security

Kensington Slot for use with Kensington locks

Part Number Part Description

CD7526 Zero Client, Dual Display, Fiber G0900340



Delivers full desktop quality computing experience via an IP connection to Blade PCs or VMware Horizon based hosts



Centralizes the PC resources in a single, secure location









Rear View

SIMPLE AND SECURE

AES-256 Suite B Ciphers, 6 USB 2.0 devices, and full power management with Wake-on-LAN support are supported by CD7526's TERA2321 chip.

CD7526 Zero Clients work with existing Ethernet networks and have two DVI connectors (1 DVI-D and 1 DVI-I). This great desktop package comes with 4 front Type-A USB 2.0 ports and 2 rear Type-A USB 2.0 ports.

OUTSTANDING USER EXPERIENCE

ClearCube delivers high performance and robust security in a new PCoIP TERA2 computing solution unhindered by distance. Support for dual monitors and full performance video, CD7526 connects to VMware® virtual desktops on SmartVDI systems, 3rd party virtual machines, and remote ClearCube Blade PCs.

In ClearCube Centralized and Virtualized Desktop Infrastructures, CD7526 can broker a connection to both SmartVDI and Blade PC resources using VMware Horizon. Dedicated 1:1 users can take advantage of hardware accelerated PCoIP.

CD7526 Zero Client requires no special OS drivers. There are no moving parts that can fail and no removable parts that encourage user tampering/theft. The units easily connect all standard peripherals including multiple monitors, keyboard, mouse, audio input/output devices and USB peripherals.

HIGH PERFORMANCE, OPTIMAL QUALITY

CD2022/24 Zero Clients deliver simultaneous full screen, full motion video at high resolution on one or two monitors. Each monitor is independently configurable for both resolution and choice of portrait or landscape orientation. Supported resolutions are single at 4K UHD 15FPS using a single display port cable or dual at 1920x1200 using two cables.

Ordering Information CALL: (866) 652-3500

Email: sales@clearcube.com to order or for more information































