



CLEARCUBE

Budget friendly quad zero client.
Outstanding user experience.



CD9552 Zero Client

KEY FEATURES

Chipset
Teradici TERA2140 PCoIP®

Display/Resolution
Single: 4K UHD 30FPS
Dual: 4K UHD 15FPS
Quad: 1920x1200

I/O Physical
DisplayPort × 4
USB 2.0 × 4
HD Audio Out and Audio In
3.5mm Speaker port × 1
3.5mm Microphone port × 1
3.5mm Headphone port × 1

Network
LAN: RJ-45, 10/100/1000 BASE-T Gigabit Ethernet
Ethernet Power connection for auto-sensing

TECHNICAL SPECS

Weight
2.5 lbs (1.13kg)

Dimensions
1.8 (W) × 7.2 (H) × 5.2 (D) in

Environment
Stationary office installation, 0° to 35° C

Power
Universal 100-240 VAC, 50-60Hz
Output: 12V DC

Max Consumption
Power adapter 12 Watts
Single-link DVI-I — 1

Physical Characteristics
Plastic housing

Operating System
None

Security
Kensington Slot for use with Kensington locks

IDEAL FOR:

- State & Local Government
- IT Professionals
- Military & Defense
- Command & Control Centers
- Healthcare, Financial, & Insurance
- Call Centers

Part Number	Part Description
G0900328	CD9552 Zero Client, Quad DisplayPorts, Copper


BENEFITS



Delivers full desktop quality computing experience via an IP connection to Blade PCs or VMware Horizon based hosts



Centralizes the PC resources in a single, secure location



4 DisplayPorts



Optional Power over Ethernet (PoE)


Rear View

▶▶▶ SIMPLE, SECURE INSTALLATION

CD9552 Zero Client requires no special OS drivers. There are no moving parts that can fail and no removable parts that encourage user tampering/theft. The units easily connect all standard peripherals including multiple monitors, keyboard, mouse, audio input/output devices and USB peripherals. Advanced configuration options allow specific policy-based management of USB devices including enabling/disabling entire classes of mass storage devices.

OUTSTANDING USER EXPERIENCE

ClearCube® delivers high performance and robust security in a new PCoIP TERA2 computing solution unhindered by distance. With quad-monitors and full performance video, CD9552 connects to VMware virtual desktops on SmartVDI systems, 3rd party virtual machines, and remote ClearCube Blade PCs.

In ClearCube Centralized and Virtualized Desktop Infrastructures (CVDI), CD9552 can broker a connection to both SmartVDI and Blade PC resources using VMware Horizon. Dedicated 1:1 users can take advantage of hardware accelerated PCoIP chips in ClearCube Blade PCs to support legacy, mission-critical, and/or GPU-intensive applications. AES-256 Suite B Ciphers, USB 2.0 devices, and full power management with Wake-on-LAN support are supported by CD9552's TERA2140 chip.

CD9552 Zero Clients work with existing Ethernet networks and have four DisplayPort connectors.

HIGH PERFORMANCE, OPTIMAL QUALITY

CD9552 Zero Clients deliver simultaneous full screen, full motion video at high resolution on two or four monitors. Each monitor is independently configurable for both resolution and choice of portrait or landscape orientation. Supported resolutions are 4K UHD 30FPS, 2x 4K UHD 15FPS or 4x 1920x1200.

Ordering Information CALL: (866) 652-3500

Email: sales@clearcube.com to order or for more information

