



CLEARCUBE

## Zero Client CD9722/24

### Built Tough Dual Copper Zero Client for Centralized and Virtualized Computing

ClearCube® delivers high performance and robust security in a new PCoIP TERA2 computing solution unhindered by distance. With dual-monitors and full-performance video, Cloud Desktop 9722 (CD9722) connects to VMware® virtual desktops on SmartVDI systems, 3<sup>rd</sup> party virtual machines, and remote ClearCube Blade PCs. CD9724 integrates a PKI-approved CAC/SIPRnet token reader that supports 5v, 3v, and 1.8v smart cards.



### Rugged, Durable Enclosure

Designed to tolerate rough use, CD9724's metal chassis is durable and oriented for CAC/SIPR card insertion. All ClearCube Desktop Zero Clients are fully TAA-compliant.

In ClearCube Centralized and Virtualized Desktop Infrastructures (CVDI), CD9722/24 can broker a connection to both SmartVDI and Blade PC resources using VMware Horizon. Dedicated 1:1 users can take advantage of hardware accelerated PCoIP chips in ClearCube Blade PCs to support legacy, mission-critical, and/or GPU-intensive applications.

AES-256 Suite B Ciphers, USB 2.0 devices, and full power management with Wake-on-LAN support are supported by CD9722/24's TERA2321 chip. A reset/power button located on the CD9722/24 Zero Clients can be selectively configured to allow or disallow users to power down or reset the connected Blade PC without administrator assistance. A separate LED link light indicates when the unit has an active connection to a PC blade or VMware View host.



### Benefits



- Delivers full desktop quality computing experience via an IP connection to Blade PCs or VMware Horizon based hosts
- Centralizes PC resources in a single, secure location



- Increases security of physical and data assets
- Rugged, all metal enclosure
- Stronger AES256-bit encryption
- CD9724 has integrated smart card reader



- Dual DVI ports (no DisplayPort cable converter)



- Provides all the benefits of a standard PC with no noise, less heat, and less space



- ClearCube Zero Clients are fully TAA-compliant.
- Industry's only advanced ship replacement warranty (CONUS)



### Full PC Experience over IP

CD9722/24 Zero Clients work with existing Ethernet networks and have two standard DVI ports (no DisplayPort converter cable needed).

# Zero Client

## Models CD9722/24

### High Performance, Optimal Quality

CD9722 Zero Clients deliver simultaneous full screen, full motion video at high resolution on one or two monitors. Each monitor is independently configurable for both resolution and choice of portrait or landscape orientation. Supported resolutions are 1x 2560x1600 or 2x 1920x1200.

### Simple Installation, Secure Hardware

CD9722 Zero Client requires no special OS drivers. There are no moving parts that can fail and no removable parts that encourage user tampering/theft. The units easily connect all standard peripherals including multiple monitors, keyboard, mouse, audio input/output devices and USB peripherals. Advanced configuration options allow specific policy-based management of USB devices including enabling/disabling entire classes of mass storage devices.



CD9724w/ attached DVD player and mounting carriage

### CD9722/24 Zero Client Specifications

<b>Chipset</b>	Teradici TERA2321 PCoIP®
<b>Operating System</b>	None
<b>Display</b>	Single: 2560x1600@60Hz, Color Depth: 8, 15, 16 or 24bpp Dual: 1920x1200@60Hz, Color Depth: 8, 15, 16 or 24bpp
<b>I/O Physical</b>	Single-link DVI-D × 1 Single-link DVI-I × 1 CD9722: USB 2.0 × 4 CD9724: USB 2.0 × 3 3.5mm Speaker port × 1 3.5mm Microphone port × 1 3.5mm Headphone port × 1
<b>Network</b>	LAN: RJ-45, 10/100/1000 BASE-T Ethernet Power connection for auto-sensing power adapter
<b>Max Consumption</b>	15 Watts (Avg 6W)
<b>Power Supply</b>	Universal 100-240 VAC, 50-60Hz Output: 12 V DC, 3A
<b>Security</b>	Kensington® Slot for use with Kensington locks Integrated PKI approved smart card reader on CD9724
<b>Environment</b>	Stationary office installation, 0° to 35° C
<b>Physical Characteristics</b>	Metal, cold-rolled steel, post plate clear zinc
<b>Dimension</b>	1.6 (W) × 6.5 (H) × 5.3 (D) inches
<b>Accessories</b>	Zero Client 7 Port USB Module DVD Player / Carriage Tray Mounting Bracket

### Ordering Information

Use the following part numbers to order

#### Model CD9722/24 Zero Client Ordering Information

Model No.	Part Number	Part Description
CD9722	G0900284	Model CD9722 Zero Client, Dual Display Copper.
CD9724	G0900285	Model CD9724 Zero Client, Dual Display Copper, w SIPR

Call: (866) 652-3500

Email: [sales@clearcube.com](mailto:sales@clearcube.com)

to order or for more information.

**Kensington®**