

A Dynamic Thin Client with Three Display Screens and **Expansion Options for High-End VDI Performance**



Thin Client CD8840

IDEAL FOR:

- State & Local Government
- IT Professionals
- Military & Defense
- Command & Control Centers
- Healthcare, Financial, & Insurance
- Call Centers
- · Oil & Gas

KEY FEATURES

CPU

Intel Celeron N3160 (4C/4T, 1.60GHz up to 2.24GHz, 6W)

Operating System StratodeskNoTouchOS/ ClearCubeCloudDesktopOS Windows10IoT Linux

Video

Max Resolution: 1 x 4K Recommended Resolution: 3 x 2560x1600

External Ports 2 x HDMI 1 x DP 1 x 3.5mm Mic 2 x USB 3.0 4 x USB 2.0 2 x RJ45 1 Gbps 2.4G/5G dual-band Wifi, Bluetooth 4.0 2 x DB9 RS232 COM

TECHNICAL SPECS

Weight 1.5 lbs. (0.6 kg)

Dimensions 1.52" (H) x 5" (L) x 5.3" (W) inches

Environment -20°C to 70°C (-4°F to 140°F)

Power Input: 100-240V AC-50/60Hz Output: DC12V/3Av

Physical Characteristics

Metal housing

Memory Type: DDR3 Recommended: 8GB


Storage SATA 2.5": Available mSATA: Available

Part Number **Part Description** CD8840 - G0900458



ENEFITS

0





Browser-based Desktop Management with real-time monitoring, asset management, and job scheduling

Dual HDMI outputs manage two displays at one location

Compact form

o∘ III

factor reduces

desktop footprint





Support for two Gigabit LAN and Wake-on-LAN support

Intel® Celeron N3150 @ 2.08GHz processor with Intel® HD graphics for powerful multimedia and a PC-like user experience

©2022 ClearCube Technology, Inc. | 1505 Volta Drive, Suite 100 Cedar Park, TX 78641 | Voice: 512.652.3500 | Fax: 512.652.3501 | www.clearcube.com





Rear View



To address environmental considerations, the CD8840 can operate in a temperature of 0 to 70°C with a thermal envelope of 6W TDP for demanding environments. The RS-232 COM port integrates high-speed data transmission and is widely used to interface with industrial or healthcare hardware. Additionally, it connects peripherals such as receipt printers, barcode scanners, drum scanners, plotters, as well as 3D printers.

The CD8840 Thin Client keeps your data secure across your workloads and workflows with built-in security. You can choose the ideal fit for specific users and environment demands with a variety of configuration options.

FEATURING INTEL® CELERON® N3160 QUAD-CORE CPU

The CD8840 Thin Client empowers enterprises with performance capabilities that conquers every task. It incorporates responsive system memory, native support for three high-resolution displays and six USB ports in a sleek, compact design featuring an all alloy chassis.

CD8840's Intel® Celeron® N3160 quad core CPU and high-performance graphics deliver the required processing power to enable smarter working, while offering a PC-like experience for standard, mid-range, and high-end applications. CD8840 Thin Clients integrate an extensive set of I/O ports for robust connectivity and quick data transfer, and are optimized for major remote connection protocols.

DESIGNED FOR THE INDUSTRIAL WORSPACE

Protect firmware, encrypt data, and lock down access with the inherently secure CD8840 Thin Client. It features a ruggedized aluminum housing structure that makes for a small attack surface while safeguarding against impacts and allowing for maximum productivity.

The small form factor of the CD8840 Thin Client fits just about anywhere administrators can mount it on the back of a monitor or a wall for reliable, enterprise grade performance. The CD8840 Thin Client design eliminates fans and vents to protect against dust particles and prevent the ingress of foreign materials. Its fanless design produces practically no noise, making the CD8840 an ideal Thin Client for quiet offices or dusty environments.

Ordering Information: CALL 512.652.3500



Email: sales@clearcube.com to order or for more information









Command 8 Control Centers



Financial Services



Education



Medical Technology







Defense





Oil & Gas



Small & Mediun

Business

Media & Entertainmen

©2022 ClearCube Technology, Inc. | 1505 Volta Drive, Suite 100 Cedar Park, TX 78641 | Voice: 512.652.3500 | Fax: 512.652.3501 | www.clearcube.com