



Multiple protocol options in a traditional zero client.
Acts like a thin client - secure like a zero.



CD7024 Zero+ Client

KEY FEATURES

CPU

Intel E3940 (4C/4T, 1.6GHz up to 1.8GHz, 9.5W)

Operating System

Stratodesk
IGEL
Win10 IoT
Windows 10 Pro
Windows 11 Pro

Video

Max Resolution Single:
3840x2160 @ 30Hz
Recommended Resolution:
2 x 2560x1600

External Ports

2 x DP
Mic+Speaker 3.5mm
4 x USB 3.0
2 x USB 2.0
1 x SFP-Fiber/Copper 1Gbps
Optional WiFi5
SmartCard Reader

Memory

4GB/8GB

Storage

eMMC: 64GB

TECHNICAL SPECS

Weight

1.12 lbs. (0.5 kg)

Dimensions

1.5" (H) x 6.5" (W) x 5" (D)

Environment

-20°C to 70°C (-4°F to 140°F)

Power

DC 19V/3A external power adapter
Max Power Consumption: 12.8W

Physical Characteristics

Metal housing

Security

Kensington Slot for use with Kensington locks
Integrated PKI approved smart card reader on CD7034

Regulatory Compliance

TAA Compliant

IDEAL FOR:

- State & Local Government
- IT Professionals
- Military & Defense
- Command & Control Centers
- Healthcare, Financial, & Insurance
- Call Centers
- Oil & Gas

Part Number	Part Description
G0907022	CD7022 Fiber ZERO+ Client
G0907024	CD7024 Fiber ZERO+ Client w CAC reader

*Max resolution may vary, depending on operating system **Onboard RJ45 option available (MOQ 100 units)

BENEFITS



Delivers full desktop computing experience via an IP connection to Blade PCs or VMware Horizon desktop with no noise, less heat, and in a small space



Soldered down eMMC improves data and hardware security.



Supports Citrix® Xen Desktop, VMware® View with Blast Extreme and PCoIP®, and others.



Centralizes PC resources in a single, secure location; increases security of physical and data assets



7 USB ports add-on and DVD drive add-on available


Rear View

SECURITY FEATURES

Security features include an integrated PKI-approved CAC reader that supports 5V, 3V, and 1.8V smartcards for enhanced user-to-network and user-to-application authentication. The 100/1000 BASE-X SFP fiber-optic network module (with LC optical interface) provides increased data security and integrity, and an integrated Kensington® Security Slot provides added anti-theft security. Firmware and data security is hardened with TPM 2.0 IC support and by featuring an embedded, non-removable eMMC flash memory soldered directly to the ZERO+ Client printed circuit board. Clearcube Desktop Zero Clients are fully TAA Compliant.

SECURE, NON-REMOVABLE ATOMX5-E3940 QUAD-CORE PROCESSOR

Designed with users in mind, CD7022/24 ZERO+ clients are powered by efficient Intel Atom x5-E3940 quad-core processors with built-in Intel HD 500 series graphics and up to 64GB soldered eMMC storage to deliver excellent computing, ultra-high definition graphics and PC-like user experience. CD7022/24 ZERO+ Clients are small endpoint devices that enable users to work on powerful computers or VMs that are remotely located in secure data centers without compromising end user experience or productivity, and providing IT Administrators a reliable device that requires minimal administration and support and the flexibility to choose from a wide range of remote display protocols.

FEATURE RICH, MULTIPLE PROTOCOLS

The CD7022/24 I/O ports include four USB 3.0 ports and two USB 2.0 ports (six total), one GbE LC fiber-optic LAN port, 3.5 mm audio input and output jacks, and two dual mode DisplayPort 1.2 (DisplayPort++) connectors to support up to two 4K full motion video displays. DisplayPort++ connectors accept passive adapters to deliver HDMI and DVI signals. Expansion options include an internal WLAN module (Wi-Fi 2.4G and 5G, Bluetooth 5.0) and an optional DVD drive/writer or 7 USB ports add-on.

Ordering Information: CALL 512.652.3500

Email: sales@clearcube.com to order or for more information



Supply Chain & Manufacturing



Command & Control Centers



Government Agencies



Financial Services



Training & Education



Healthcare & Medical Technology



Engineering & Design



Department of Defense



Digital Signage



Oil & Gas



Small & Medium Business



Media & Entertainment