

Future proof your display options.

6 USB 2.0 Ports (4 in front, 2 in back) with ability to independently configure monitors.



Zero Client CD7526

IDEAL FOR:

- State & Local Government
- IT Professionals
- · Military & Defense
- · Command & Control Centers
- Healthcare, Financial, & Insurance
- · Call Centers
- · Oil & Gas

Part Number Part Description

G0900340 - CD7526

KEY FEATURES

Chipset

Teradici TERA2321 PCoIP

Video

Single: 2560x1600 Dual: 1920x1080

External Ports

2 x DVI

Mic+Speaker 3.5mm

6 x USB 2.0

1 x SFP-Fiber/Copper 1Gbps

Memory

512MB

Storage

256Mbit

TECHNICAL SPECS

Weight

1 lbs.

Dimensions

1.8" (H) x 5.9" (W) x 5.1" (D)

Environment

-20°C to 70°C (-4°F to 140°F)

Power

Universal 100-240 VAC, 50-60Hz

Output: 12V DC, 3A

Physical Characteristics

Plastic

Security

Kensington Slot for use with Kensington locks Integrated PKI approved smart card reader on CD7034



0



Delivers full desktop computing experience via an IP connection to Blade PCs or VMware Horizon desktop with no noise, less heat, and in a small space





Supports Citrix® Xen Desktop, VMware® View with Blast Extreme and PCoIP®, and others.



Centralizes PC resources in a single, secure location; increases security of physical and data assets





Rear View

SIMPLE AND SECURE

AES-256 Suite B Ciphers, 6 USB 2.0 devices, and full power management with Wake-on-LAN support are supported by CD7526's TERA2321 chip.

CD7526 Zero Clients work with existing Ethernet networks and have two DVI connectors (1 DVI-D and 1 DVI-I). This great desktop package comes with 4 front Type-A USB 2.0 ports and 2 rear Type-A USB 2.0 ports.

OUTSTANDING USER EXPERIENCE

ClearCube delivers high performance and robust security in a new PCoIP TERA2 computing solution unhindered by distance. Support for dual monitors and full performance video. CD7526 connects to VMware virtual desktops on SmartVDI systems, 3rd party virtual machines, and remote ClearCube Blade PCs.

In ClearCube Centralized and Virtualized Desktop Infrastructures, CD7526 can broker a connection to both SmartVDI and Blade PC resources using VMware Horizon. Dedicated 1:1 users can take advantage of hardware accelerated PCoIP.

CD7526 Zero Client requires no special OS drivers. There are no moving parts that can fail and no removable parts that encourage user tampering/theft. The units easily connect all standard peripherals including multiple monitors, keyboard, mouse, audio input/output devices and USB peripherals.

HIGH PERFORMANCE, OPTIMAL QUALITY

CD7526 Zero Clients deliver simultaneous full screen, full motion video at high resolution on one or two monitors. Each monitor is independently configurable for both resolution and choice of portrait or landscape orientation. Supported resolutions are single at 4K UHD 15FPs using a single display port cable or dual at 1920x1200 using two cables.

Ordering Information: CALL 512.652.3500

Email: sales@clearcube.com to order or for more information

























