



Zero Client CD9522

Budget friendly zero client for virtual desktop infrastructure and remote computing
No special OS drivers, no moving parts that fail, with 2 standard DVI ports.

KEY FEATURES

Chipset

Teradici TERA2321 PCoIP

Video

Single: 2560x1600
Dual: 1920x1080

External Ports

2 x DVI-D
Mic+Speaker 3.5mm
4 x USB 2.0
1 x 1Gbps RJ45

Memory

512MB

Storage

256Mbit

TECHNICAL SPECS

Weight

1 lbs.

Dimensions

1.8" (H) x 5.9" (W) x 5.1" (D)

Environment

-20°C to 70°C (-4°F to 140°F)

Power

Universal 100-240 VAC, 50-60Hz
Output: 12V DC, 3A

Physical Characteristics

Plastic

Security

Kensington Slot for use with Kensington locks
Integrated PKI approved smart card reader on CD7034

IDEAL FOR:

- State & Local Government
- IT Professionals
- Military & Defense
- Command & Control Centers
- Healthcare, Financial, & Insurance
- Call Centers
- Oil & Gas

Part Number Part Description

G0900251 - CD9922

BENEFITS



Delivers full desktop computing experience via an IP connection to Blade PCs or VMware Horizon desktop with no noise, less heat, and in a small space



Soldered down eMMC improves data and hardware security.



Supports Citrix® Xen Desktop, VMware® View with Blast Extreme and PCoIP®, and others.



Centralizes PC resources in a single, secure location; increases security of physical and data assets



7 USB ports add-on and DVD drive add-on available


Rear View

SIMPLE INSTALLATION & SECURE HARDWARE

ClearCube delivers high performance and robust security in a new PCoIP TERA2 computing solution unhindered by distance. With dual monitors and full-performance video, CD9522 connects to VMware virtual desktops on SmartVDI systems, 3rd-party virtual machines, and remote ClearCube Blade PCs.

In ClearCube Centralized and Virtualized Desktop Infrastructures (CVDI), VMware Horizon can broker connections from CD9522 zero clients to both SmartVDI and Blade PC resources. Dedicated 1:1 users can take advantage of hardware accelerated PCoIP chips in ClearCube Blade PCs to support legacy, mission-critical, and/or GPU-intensive applications.

The CD9522 TERA2321 chip supports AES-128/AES-256 Suite B Ciphers, USB 2.0 devices, and full power management with Wake-on-LAN support.

WORKS WITH EXISTING NETWORKS

CD9522 Zero Clients work with existing Ethernet networks and have two standard DVI ports (no display port converter cable needed).

OPTIMAL QUALITY

CD9522 Zero Clients deliver simultaneous full-screen, full-motion video at high resolution. Users can configure a different resolution and orientation (landscape or portrait) for each monitor. Supported resolutions include one display at 2560x1600 or two displays at 1920x1200.

HIGH PERFORMANCE, OPTIMAL QUALITY

CD9522 Zero Client requires no special OS drivers. There are no moving parts that can fail and no removable parts that encourage user tampering or theft. The units easily connect all standard peripherals including multiple monitors, keyboard, mouse, audio input/output devices and USB peripherals. Advance configuration options allow management of USB devices including enabling/disabling entire classes of mass storage devices.

Ordering Information: CALL 512.652.3500

Email: sales@clearcube.com to order or for more information



Supply Chain & Manufacturing



Command & Control Centers



Government Agencies



Financial Services



Training & Education



Healthcare & Medical Technology



Engineering & Design



Department of Defense



Digital Signage



Oil & Gas



Small & Medium Business



Media & Entertainment