Datasheet



Zero Client CD9552

IDEAL FOR:

- State & Local Government
- IT Professionals
- Military & Defense
- Command & Control Centers
- Healthcare, Financial, & Insurance
- Call Centers
- Oil & Gas

Part Number **Part Description** G0900328 - CD9552

ENEFITS 8

Delivers full desktop computing experience via an IP connection to Blade PCs or VMware Horizon desktop with no noise, less heat, and in a small space





Supports Citrix® Xen Desktop, VMware® View with Blast Extreme and PCoIP®, and others.

TECHNICAL SPECS

Weight 1.75 lbs.

Dimensions 1.7" (H) x 7.2" (W) x 5.2" (D)

Environment -20°C to 70°C (-4°F to 140°F)

Power Universal 100-240 VAC, 50-60Hz Output: 12V DC, 3A

Physical Characteristics

Plastic

Security

Kensington Slot for use with Kensington locks Integrated PKI approved smart card reader on CD7034



Centralizes PC resources in a single, secure location; increases security of physical and data assets

7 USB ports add-on and DVD drive addon available

©2022 ClearCube Technology, Inc. | 1505 Volta Drive, Suite 100 Cedar Park, TX 78641 | Voice: 512.652.3500 | Fax: 512.652.3501 | www.clearcube.com

CLEARCUBE **Budget Friendly Quad Zero Client** Outstanding user experience.

KEY FEATURES

Single: 3840x2160

Mic+Speaker 3.5mm

Dual: 2560x1600 Quad: 1920x1080

External Ports

1 x 1Gbps RJ45

4 x USB 2.0

Memory 512MB

Storage

256Mbit

Teradici TERA2140 PCoIP

Chipset

Video

4 x DP





Rear View

SIMPLE AND SECURE

CD9552 Zero Client requires no special OS drivers. There are no moving parts that can fail and no removable parts that encourage user tampering/theft. The units easily connect all standard peripherals including multiple monitors, keyboard, mouse, audio input/output devices and USB peripherals. Advanced configuration options allow specific policy-based management of USB devices including enabling/disabing entire classes of mass storage devices.

FULL PC EXPERIENCE OVER IP

ClearCube delivers high performance and robust security in a new PCoIP TERA2 computing solution unhindered by distance. With quad-monitors and full performance video, CD9552 connects to VMware virtual desktops on SmartVDI systems, 3rd party virtual machines, and remote ClearCube Blade PCs.

In ClearCube Centralized and Virtualized Desktop Infrastructures (CVDI), CD9552 can broker a connection to both SmartVDI and Blade PC resources using WMware Horizon. Dedicated 1:1 users can take advantage of hardware accelerated PCoIP chips in ClearCube's Blade PCs to support legacy, mission-critical, and/or GPU-intensive applications.

AES-256 Suite B Ciphers, USB 2.0 devices, and full power management with Wake-on-LAN support are supported by CD9552's TERA2140 chip. CD9542 Zero Clients work with existing Ethernet networks and have four DisplayPort connectors.

HIGH PERFORMANCE, OPTIMAL QUALITY

CD9552 Zero Clients deliver simultaneous full screen, full motion video at high resolution on two or four monitors. Each monitor is independently configurable for both resolution and choice of portrait or landscape orientation. Supported resolutions are 2 x 2560x1600 or 4 x 1920x1200.

Ordering Information: CALL 512.652.3500

Email: sales@clearcube.com to order or for more information















Education





Design







Oil & Gas





AA Compliant

assembled & tester

in the

Command & Control Centers

Services

Healthcare & Medical Technology

Engineering &

Department of Defense

Small & Medium Business

Media & Entertainment