

Save time, money, and simplify management.

Get connected easier and fasther with a secure, reliable device.



Zero Client CD9524M

IDEAL FOR:

- State & Local Government
- IT Professionals
- · Military & Defense
- · Command & Control Centers
- · Healthcare, Financial, & Insurance
- · Call Centers
- · Oil & Gas

Part Number Part Description

G0900452 - CD9522M G0900398 - CD9524M

KEY FEATURES

Chipset

Teradici TERA2321 PCoIP

Video

Single: 2560x1600 Dual: 1920x1080

External Ports

1 x DVI

1 x DP

Mic+Speaker 3.5mm

6 x USB 2.0

1 x 1Gbps RJ45

SmartCard Reader

Memory

512MB

Storage

256Mbit

TECHNICAL SPECS

Weight

1.5 lbs.

Dimensions

1.5" (H) x 6.5" (W) x 5" (D)

Environment

-20°C to 70°C (-4°F to 140°F)

Power

DC 19V/3A external power adapter Max Power Consumption: 12.8W

Physical Characteristics

Metal housing

Security

Kensington Slot for use with Kensington locks Integrated PKI approved smart card reader on CD7034

Regulatory Compliance

TAA Compliant



0



Delivers full desktop computing experience via an IP connection to Blade PCs or VMware Horizon desktop with no noise, less heat, and in a small space



Soldered down eMMc improves data and hardware security.



Supports Citrix® Xen Desktop, VMware® View with Blast Extreme and PCoIP®, and others.



Centralizes PC resources in a single, secure location; increases security of physical and data assets





Rear View



IMPRESSIVE COMPUTING

The CD9522/24M's most powerful TERA2321 chip supports AES-128/AES-256 Suite B Ciphers for exceptional security, 6 USB ports, one DisplayPort connector and one DVI-I connector to support one display at 4K resolution (DisplayPort only), and two displays at 1920x1200 resolution, and full power management with Wake-on-LAN features.

FULL PC EXPERIENCE OVER IP

ClearCube CD9522/24M delivers high performance and robust security in a PCoIP Teradici TERA2 computing graphics and video on dual monitors and connects over copper networks to VMware virtual desktops, servers, Blade PCs or public cloud resources brokered by VMware Horizon. Dedicated 1:1 users (where one person uses one dedicated computer) can take advantage of hardware accelerated PCoIP host cards in ClearCube Blade PCs to support legacy, mission-critical, and GPU intensive applications.

SIMPLE INSTALLATION

CD9522/24M Zero Client requires no specail OS drivers and there are no moving parts that can fail. There is added protection with zero removable parts that discourage user tampering or theft. The units support low speed USB peripherals including multiple monitors, keyboard, mouse, audio input/output devices, and more. The end results is a fanless and reliable client-side device that requires minimal IT administration and support.

SECURE HARDWARE

Additional security features on the CD9524M includes an integrated PKI-approved CAC reader that supports 5V, 3V, and 1.8V smart cards for enhanced user-to-network an user-to-application authentication and keeps users from spending valuable time repeatedly logging into computers.

Ordering Information: CALL 512.652.3500

Email: sales@clearcube.com to order or for more information

























