



Budget Friendly Dual Fiber Zero Client
Great for Centralized and Virtualized Desktop Infrastructure



Zero Client CD7522P

IDEAL FOR:

- State & Local Government
- IT Professionals
- Military & Defense
- Command & Control Centers
- Healthcare, Financial, & Insurance
- Call Centers
- Oil & Gas

Part Number Part Description

G0900261 - CD7522P

KEY FEATURES

Chipset
Teradici TERA2321 PCoIP

Video
Single: 2560x1600
Dual: 1920x1080

External Ports
2 x DVI
Mic+Speaker 3.5mm
4 x USB 2.0
1 x SFP-Fiber/Copper 1Gbps

Memory
512MB

Storage
256Mbit

TECHNICAL SPECS

Weight
1.75 lbs.

Dimensions
1.8" (H) x 5.9" (W) x 5.1" (D)

Environment
Storage Temperature: -20°C to 70°C (-4°F to 140°F)
Operating Temperature: 0°C to 40°C (32F to 104°F)

Power
Universal 100-240 VAC, 50-60Hz
Output: 12V DC, 3A

Physical Characteristics
Plastic

Security
Kensington Slot for use with Kensington locks
Integrated PKI approved smart card reader on CD7034

BENEFITS



Delivers full desktop computing experience via an IP connection to Blade PCs or VMware Horizon desktop with no noise, less heat, and in a small space



No open storage, only firmware configuration



Supports remote workstation cards, and HP Anyware, and VMware PCoIP



Fully TAA compliant


Rear View

▶▶▶ SIMPLE AND SECURE

CD7522 Zero Client requires no special OS drivers. There are no moving parts that can fail and no removable parts that encourage user tampering/theft. The units easily connect all standard peripherals including multiple monitors, keyboard, mouse, audio input/output devices and USB peripherals. Advanced configuration options allow specific policy-based management of USB devices including enabling/disabling entire classes of mass storage devices.

DUAL FIBER ZERO CLIENT

ClearCube delivers high performance and robust security in a new PCoIP TERA2 computing solution unhindered by distance. With dual-monitors and full performance video, CD7522 connects to VMware virtual desktops on SmartVDI systems, 3rd party virtual machines, and remote ClearCube Blade PCs.

In ClearCube Centralized and Virtualized Desktop Infrastructures (CVDI), CD7522 can broker a connection to both SmartVDI and Blade PC resources using VMware Horizon. Dedicated 1:1 users can take advantage of hardware accelerated PCoIP chips in ClearCube's Blade PCs to support legacy, mission-critical, and/or GPU-intensive applications. CD7522 Zero Client's SFPs support 100 Base and 1000 Base connections to host resources.

AES-256 Suite B Ciphers, USB 2.0 devices, and full power management with Wake-on-LAN support are supported by CD7522's TERA2321 chip.

HIGH PERFORMANCE, OPTIMAL QUALITY

CD7522 Zero Clients deliver simultaneous full screen, full motion video at high resolution on one or two monitors. Each monitor is independently configurable for both resolution and choice of portrait or landscape orientation. Supported resolutions are 2 x 2560x1600 or 4 x 1920x1200.

Ordering Information: CALL 512.652.3500

Email: sales@clearcube.com to order or for more information



Supply Chain & Manufacturing



Command & Control Centers



Government Agencies



Financial Services



Training & Education



Healthcare & Medical Technology



Engineering & Design



Department of Defense



Digital Signage



Oil & Gas



Small & Medium Business



Media & Entertainment