

# Future proof your display options.

# Dual DisplayPort, Fiber/Copper Zero+® Client, 6 USB Ports and an integrated CAC Reader.



Zero+® Client CD7042/44

## **IDEAL FOR:**

- Government, Military & Defense
- IT Professionals
- Command & Control
- Helthcare, Financial & Insurance

Part Number Part Description

**CD7042** - CD907042 **CD7044** - CD907044

## **KEY FEATURES**

#### CPU

Intel Atom x6413E (4C/4T, 1.5GHz up to 3.0GHz, 9W)

## **Operating System**

Stratodesk

**IGEL** 

Win10 IoT

Windows 10 Pro

Windows 11 Pro

#### Video

Max Resolution Single:

3840x2160 @ 60Hz

Recommended Resolution:

2 x 3840x2160 @ 60Hz

#### **External Ports**

2 x DP

Mic+Speaker 3.5mm

3 x USB 3.0 (1 x USB-C)

2 x USB 2.0

1 x SFP-Fiber/Copper 1Gbps

Optional WiFi5

SmartCard Reader

### Memory

8GB

#### Storage

eMMC: 64GB

### **TECHNICAL SPECS**

### Weight

1.12 lbs. (0.5 kg)

#### **Dimensions**

1.5" (H) x 6.5" (W) x 5" (D)

#### **Environment**

Storage Temperature: -20°C to 70°C (-4°F to 140°F) Operating Temperature: 0°C to 40°C (32F to 104°F)

#### **Power**

12 V DC

#### **Physical Characteristics**

Metal housing

#### Security

Kensington Slot for use with Kensington locks Integrated PKI approved smart card reader on CD7034

### **Regulatory Compliance**

**TAA Compliant** 





Delivers full desktop computing experience via an IP connection to Blade PCs or VMware Horizon desktop with no noise, less heat, and in a small space



No removable storage, only firmware configuration



Supports VMware Horizon with Blast Extreme, CITRIX, HDX, Microsoft RDP



Smart card reader with SIPR token support



7 USB ports add-on and DVD drive add-on available



**Rear View** 



# **SECURITY FEATURES**

Security features include integrated an PKI-approved CAC reader that supports 5V, 3V, and 1.8V smartcards for enhanced user-to-network user-to-application and authentication. The 100/1000 BASE-X SFP fiber-optic network module (with LC optical interface) provides increased data integrity, and an integrated security and Kensington® Security Slot provides added anti-theft security. Firmware and data security is hardened with TPM 2.0 IC support and by featuring embedded, non-removable eMMC flash memory soldered directly to the Zero+® Client printed circuit board. Clearcube Desktop Zero Clients are fully TAA Compliant.

# ULTRA THIN SMALL FORM FACTOR DEVICE WITH SECURED STORAGE

Delivers a user's desktop from a centralized host server with an immaculate, uncompromised end user experience across standard IP networks including full high resolution dual monitor video, complete USB compatibility, and full duplex high definition audio, while remains a ultra thin small form factor device with secured storage.

The CD7042/44 I/O ports include four USB 3.2 ports, two USB 2.0 ports and one USB 3.2 type C port (seven total), one GbE LC fiber Optic LAN port ,3.5mm audio input and output jacks, and two dual mode DisplayPort 1.2 connectors to support up to two 4K full motion video displays. Features full SV provider compatibility, including Citrix, VMware, Teradici, and Microsoft, a variety of I/O ports and optional WIFI. Uses a soldered, non-removable embedded Multi-mediaCard (eMMC) mass storage device to secure operating system (Linux® or Windows®) and data.

Zero+® Clients are small endpoint devices that enable users to work on powerful computers or VMs that are remotely located in secure data centers without compromising enduser experience or productivity, and providing IT Administrators are liable device that requires minimal administration and support and the flexibility to choose from a wide range of remote display protocols.

# **Ordering Information: CALL 512.652.3500**

Email: sales@clearcube.com to order or for more information



























