

A Fanless Trusted Zero Client with Four Display Screens and Expansion Options for High-End VDI Performance



Thin Client CD8842-44T

IDEAL FOR:

- · Command & Control Center
- Government Agencies
- Architecture, Engineering, & Construction
- Media & Entertainment
- Healthcare
- Financial
- Digital Signage
- Training & Education

KEY FEATURES

CPU

AMD Ryzen Embedded V1605B (4C/8T, 2.0GHz up to 3.6GHz, 54W, AVX 2, Radeon Vega 11)

Operating System

HP Anyware

Video

Max Resolution: 4 x 4K @ 60Hz

Recommended Resolution: 4 x 4K @ 60Hz

External Ports

4 x DP

3 x USB 3.2 Gen1

1 x USB 3.2 Gen2

2 x USB 2.0

SFP - 1GBps

2.4G/5G dual-band Wifi, Bluetooth 4.0

Smart Card Reader (CD8844)

TECHNICAL SPECS

Weight

2.5 lbs. (1.13 kg)

Dimensions

1.66" (H) x 7.16" (L) x 6.96" (W) inches

Environment

-20°C to 70°C (-4°F to 140°F)

Power

Input: 100-240V AC-50/60Hz

Output: DC12V/3Av

Physical Characteristics

Metal housing

Memory

Type: DDR3

Recommended: 8GB (2 Sticks)

U.S. White House has directed all agencies to have a

plan to adopt a Zero Trust posture by the end of FY241.

Storage

2242NVMe/SATA

Part Number Part Description

CD8842T - G0908842T **CD8844T** - G0908844T



Delivers enhanced graphics using HP

Anyware software



Manufactured with a unique birth certificate for Zero Trust validation



Compatible with VMWare Blast, VMWare Horizon, Nutanix, KVM, Leostream, Amazon WorkSpaces, Google Cloud Platform, Microsoft HyperV, and physical computer hardware



Smart card reader with SIPR token support





REAR VIEW



SECURITY FEATURES

Not only do Trusted Zero Clients provide the very best in remoting security, but they also provide outstanding performance. Using PCoIP Ultra version of the software license. Trusted Zero Clients deliver color-accurate, lossless, and distortion-free remote user experience. The software technology automatically adapts to changing network conditions to enable the best possible user experience. It does this by balancing image fidelity, CPU utilization, and network efficiency with multicore CPU scaling to free up valuable CPU resources for heavy workloads and allow for increased server consolidation. However, it is important to note that features like SIPR token support, VMWare support, and requiring access to the outside world to become operational are not yet available in this version.

THE TRUSTED ZERO CLIENT IS OUR NEW "ZERO TRUST" ZERO CLIENT.

Like a traditional zero client, Trusted Zero Clients utilize the PCoIP protocol by HP Teradici. This protocol keeps the data in the data center by transmitting encrypted pixels between the host computer and the endpoint. This has been a critical security feature of zero clients, and it is also present with the new Trusted Zero Clients.

"Trusted" is in the title because these new zero clients adhere to the "zero trust" security principles, as recommended by NIST and similar organizations. To accomplish this, Trusted Zero Clients incorporate these security safeguards:

- First, Trusted Zero Clients come with a factory-provisioned birth certificate that is verified by HP Anyware Trust Center software before the Trusted Zero Client is granted access to the network. Once approved, Anyware Trust Center provides a new operational certificate that is also linked to an active software license. This feature prevents counterfeit devices from being connected.
- Second, firmware is locked down with direct secure boot into the Trusted Zero Clients to prevent tampering with firmware, BIOS, or OS.
- Third, a trusted connection is established with the Trusted Zero Client, and the Anyware Trust Center software continuously monitors the Trusted Zero Client for any potential security issues, such as connected peripherals, old firmware versions, or security breaches. FIPS 140-3 Level 1 and Federated Authentication are supported.

Ordering Information: CALL 512.652.3500

Email: sales@clearcube.com to order or for more information

